



Fiber Patch panel

APPLICATIONS

Fiber patch panel is applicable for straight-through connection and diverged connection in aerial layout. Duct and direct buried. Protects fiber connectors

FEATURES

- The shell is high intensified & insulated material, thus having excellent mechanic performance It is solid and durable
- Fiber input: 4
- Adapters output: 12core or 24 core or 48 core
- Strength core and shell was Insulation, add with grounding lead Suitable for inserting installation of SC, FC, ST and LC adaptor Full accessories for convenient operations

SPECIFICATIONS

- Environment temperature: $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$
- Relative humidity: $\leq 85\%$ (30°C)
- Atmosphere pressure: $70 \sim 106\text{KPa}$
- Insulated Resistance: $\geq 2 \times 10\text{Mohm}/500\text{V}$ (DC)
- Intensity $\leq 15\text{kv}$ (DC) /1minno spark-over and no flying arc
- Fiber bending radium guaranteed more than 40mm: $\geq 40\text{mm}$

PERFORMANCE

- Excellent design
- Maximum cores: 48
- fiber ready grounding and perfect fix up
- Pigtail fixes up reliable and perfect protection
- Apply to extensive field
- Convenient operations and maintenance

ORDERING INFORMATION

LZ-FLIU24U: LANZONE Fiber patch panel 24 port unloaded with splice tray, 1U height.