

## 3+1 CCTV CABLE

Lanzone offers 3+1 CCTV cables in four different models that includes copper and alloy braiding. These camera wires come with co axial cable for video signal and Power cable for electrical power supply.

The cables are designed in order to reduce the distortion and optimize the video quality.



Part Codes	LZ-C0690V
<b>DESCRIPTION</b>	<b>Lanzone 3+1, Copper braiding and video core of 0.60mm in 90 meters</b>
<b>Hook Up Core</b>	
<b>CONDUCTOR</b>	
Conductor Material	Annealed Bare Copper
No. of wire in Conductor	14
Size of strand Nominal (mm)	0.09-0.10
Annealing before stranding(minimum)%	10.50 to 12.0
<b>INSULATION</b>	
Dielectric material	PVC Type A
Colour	Red, Yellow & Blue
Nominal Diameter (mm)	1.12 to 1.13
<b>Pick UP Core</b>	
<b>CONDUCTOR</b>	
Conductor Material	Annealed Bare Copper
No. of wire in Conductor	1
Size (mm)	0.60
Annealing before stranding min.%	20.5
<b>1st INSULATION LDPE</b>	
Dielectric material	LDPE
Nominal Diameter over (mm)	1.60
Colour	Natural White
<b>BRAIDING Over LDPE Insulation</b>	
Type of Braiding Material	Copper braiding
No.of wire in braiding (No./mm)	32/.0.085-0.09
Polyester tape (mm)	6 x 0.020 mm
<b>2nd INSULATION PVC</b>	
Dielectric material	PVC Type A
Radial thickness Nom. (mm)	0.22
Colour	Black
Nominal Diameter (mm)	2.55



## 3+1 CCTV CABLE

<b>Laying UP</b>	3+1
Tapping	Polyester tape
<b>OVERALL OUTER SHEATH</b>	
Material	Extruded PVC Type ST-1
Thickness (mm)	0.72
Colour	White
Outer Sheath Diameter (Approx in mm)	5.60
Length of Coil (mtr)	90