

## **3+1 CCTV CABLE**

Lanzone offers 3+1 CCTV cables in four different models that includes copper and alloy braiding. These camera wires come with co axial cable for video signal and Power cable for electrical power supply.

The cables are designed in order to reduce the distortion and optimize the video quality.



Part Codes	LZ-C06180V.6
DESCRIPTION	Lanzone 3+1,alloy braiding and video core of 0.60mm in 180
	meters
Hook Up Core	
CONDUCTOR	
Conductor Material	Annealed Bare Copper
No. of wire in Conductor	14
Size of strand Nominal (mm)	0.095
Annealing before stranding(minimum)%	9
INSULATION	
Dielectric material	HDPE
Colour	Red, Yellow &,Blue
Nominal Diameter (mm)	1.15
Pick UP Core	
CONDUCTOR	
Conductor Material	Annealed Bare Copper
No. of wire in Conductor	1
Size (mm)	0.60
Annealing before stranding min.%	18
1st INSULATION LDPE	
Dielectric material	LDPE
Nominal Diameter over (mm)	1.63
Colour	Natural White
BRAIDING Over LDPE Insulation	
Type of Braiding Material	Aluminium alloy braiding
No.of wire in braiding (No./mm)	48/.110
Polyester tape (mm)	6 x 0.020 mm
2nd INSULATION PVC	
Dielectric material	PVC Type A
Radial thickness Nom. (mm)	0.20
Colour	Black

3+1 CCTV Cable Rev: Nil Ver: 1 Dt: 01.10.19



## 3+1 CCTV CABLE

Nominal Diameter (mm)	2.50
Laying UP	3+1
Tapping	Polyester tape
OVERALL OUTER SHEATH	
Material	Extruded PVC Type ST-1
Thickness (mm)	0.70
Colour	White
Outer Sheath Diameter (Approx in mm)	5.50
Length of Coil (mtr)	180